PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) TRACKED EXCAVATORS DX, DH DX62R-3 YANMAR 4TNV94L (2013 AND AFTER)

ENGINE Yanmar 4TNV94L
Capacity: 10,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	**Agrisynth LSP Ultra 10W-40**	**Agrisynth LSP 10W-40**

Check every 10 hours, change every 250 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	**Agrisynth LSP Ultra 10W-40**	**Agrisynth LSP 10W-40**

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 65 liter (Hydraulic tank), Capacity: 100 liter (System)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	**Perlus H 32**	

Check every 10 hours, change every 1000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) TRACKED EXCAVATORS DX, DH DX62R-3 YANMAR 4TNV94L (2013 AND AFTER)

COOLING SYSTEM
Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 10 hours, change every 2000 hours/ 24 months

SWING REDUCTION UNIT

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		

Change every 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 1000 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) TRACKED EXCAVATORS DX, DH DX62R-3 YANMAR 4TNV94L (2013 AND AFTER)

TRAVEL REDUCTION UNIT
Capacity: 1,4 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
Change every 1000 hours		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	
Change every 1000 hours		

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
Change every 250 hours		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	
Change every 250 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367