DOOSAN (DAEWOO) WHEELED LOADERS DL DL300-3 SCANIA DC9 (STAGE IIIB) (2012-



2015)

ENGINE Scania DC9 Capacity: 34 liter		
USE		CLIMATE
Normal, fuel sulfur level < 0,3 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Armado Synth 10W-40	Armado Synth 5W-30	

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT Capacity: 42 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 1500 hours		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 1000 hours		

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Agrifluid HT	
	·
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Agrifluid HT	
•	·
	Agrifluid HT PRODUCT RECOMMENDATION 2

DOOSAN (DAEWOO) WHEELED LOADERS DL DL300-3 SCANIA DC9 (STAGE IIIB) (2012-



2015)

TRANSMISSION HYDRODYNAMIC F Capacity: 54 liter	POWERSHIFT ZF 5WG230 5/3	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT
Change every 1500 hours		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT
Change every 1000 hours		

HYDRAULIC SYSTEM Capacity: 230 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Check every 10 hours, change ever	y 2000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	
Check every 10 hours, change ever	y 2000 hours	•

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) WHEELED LOADERS DL DL300-3 SCANIA DC9 (STAGE IIIB) (2012-



2015)

COOLING SYSTEM Capacity: 50 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant -38 Organic NF	Coolant -26	Coolant -33 MPG
Check every 10 hours, change every	/ 2000 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.