## DYNAPAC TRACKED PAVERS DF/F/SD DF45CS DEUTZ BF3L 2011



<b>ENGINE</b> Deutz BF3L-2011 Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 500 hours

PUMP REDUCTION UNIT Capacity: 1,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		

Check every 10 hours, change every 1500 hours

HYDRAULIC SYSTEM Capacity: 70 liter (Hydraulic tank)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Perlus H 46				
Check every 10 hours, change every 2000 hours/ 24 months				
USE		CLIMATE		
Biodegradable oil		Mediterranean		
PRODUCT RECOMMENDATION 1				

Check every 10 hours, change every 2000 hours/24 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

## **AUGER BOX**

Capacity: 2,5 liter

Perlus Biosynth 46

We are unable to give a standard recommendation for this component. Please contact our service department.

PRODUCT RECOMMENDATION

## DYNAPAC TRACKED PAVERS DF/F/SD **DF45CS DEUTZ BF3L 2011**



TRAVEL REDUCTION UNIT Capacity: 0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP 220		
Check every 250 hours, change every 1000 hours/ 12 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.