PRODUCT RECOMMENDATION

DYNAPAC TRACKED PAVERS DF/F/SD F1000T CUMMINS QSB-6.7 IIIA/T3 (717) (2011 AND AFTER)

ENGINE Cummins QSB6.7C
Capacity: 17,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	

Check every 10 hours, change every 250 hours

PUMP REDUCTION UNIT
Capacity: 5,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	**Unigear LS GL-3/GL-5 85W-140**	

Check every 50 hours, change every 1000 hours

HYDRAULIC SYSTEM
Capacity: 303 liter, Capacity: 189 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 2000 hours/ 12 months

USE	CLIMATE
Biodegradable oil	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 2000 hours/ 12 months

CENTRAL LUBRICATION UNIT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

DYNAPAC TRACKED PAVERS DF/F/SD F1000T CUMMINS QSB-6.7 IIIA/T3 (717) (2011 AND AFTER)

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM ENGINE
Capacity: 24,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant -38 Organic NF	**Coolant -26**	**Coolant -33 MPG**

Check every 10 hours, change every 2000 hours/ 24 months

AUGER ANGLE GEAR BOX
Capacity: 0,6 liter (each side)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube Racing 75W-140	**Unigear LS GL-3/GL-5 85W-140**	

Check every 250 hours, change every 2000 hours/ 24 months

AUGER REDUCTION UNIT
Capacity: 2,5 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube Racing 75W-140	**Unigear LS GL-3/GL-5 85W-140**	

Check every 250 hours, change every 2000 hours/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

DYNAPAC TRACKED PAVERS DF/F/SD F1000T CUMMINS QSB-6.7 IIIA/T3 (717) (2011 AND AFTER)

CONVEYOR GEARBOX
Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	**Unigear LS GL-3/GL-5 85W-140**	

Check every 250 hours, change every 2000 hours/ 24 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	**Unigear LS GL-3/GL-5 85W-140**	

Change every 100 hours

TRAVEL REDUCTION UNIT
Capacity: 3 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	**Unigear LS GL-3/GL-5 85W-140**	

Check every 250 hours, change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367