

# DYNAPAC TRACKED PAVERS DF/F/SD F1000T CUMMINS QSB-6.7 IIIB/T4I (2102) (2012 AND AFTER)



**ENGINE** Cummins QSB6.7C  
Capacity: 17,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2     | PRODUCT RECOMMENDATION 3      |
|-----------------------------|------------------------------|-------------------------------|
| <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> | <b>Dieselfleet MSP 15W-40</b> |

*Check every 10 hours, change every 250 hours*

**PUMP REDUCTION UNIT**  
Capacity: 5,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2            |  |
|--------------------------------|-------------------------------------|--|
| <b>Gearlube Racing 75W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Check every 50 hours, change every 1000 hours*

**HYDRAULIC SYSTEM**  
Capacity: 303 liter, Capacity: 189 liter (Hydraulic tank)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Perlus H 46</b>       |  |  |

*Check every 10 hours, change every 2000 hours/ 12 months*

| USE               | CLIMATE       |
|-------------------|---------------|
| Biodegradable oil | Mediterranean |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Perlus Biosynth 46</b> |  |  |

*Check every 10 hours, change every 2000 hours/ 12 months*

## CENTRAL LUBRICATION UNIT

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>MoS2 Grease EP 2</b>  |  |  |

# DYNAPAC TRACKED PAVERS DF/F/SD F1000T CUMMINS QSB-6.7 IIIB/T4I (2102) (2012 AND AFTER)



## GREASE POINTS/NIPPLES

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

## COOLING SYSTEM COMBUSTION ENGINE

Capacity: 24,6 liter

| USE                           |                          | CLIMATE                  |
|-------------------------------|--------------------------|--------------------------|
| Normal                        |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       | <b>Coolant -33 MPG</b>   |

*Check every 10 hours, change every 2000 hours/ 24 months*

## AUGER ANGLE GEAR BOX

Capacity: 0,6 liter (each side)

| USE                            |                                     | CLIMATE  |
|--------------------------------|-------------------------------------|----------|
| Normal                         |                                     | Moderate |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2            |          |
| <b>Gearlube Racing 75W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |          |

*Check every 250 hours, change every 2000 hours/ 24 months*

## AUGER BOX

Capacity: 2,5 liter (each)

| USE                            |                                     | CLIMATE  |
|--------------------------------|-------------------------------------|----------|
| Normal                         |                                     | Moderate |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2            |          |
| <b>Gearlube Racing 75W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |          |

*Check every 250 hours, change every 2000 hours/ 24 months*

# DYNAPAC TRACKED PAVERS DF/F/SD F1000T CUMMINS QSB-6.7 IIIB/T4I (2102) (2012 AND AFTER)

**CONVEYOR GEARBOX**

Capacity: 1,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2            |  |
|--------------------------------|-------------------------------------|--|
| <b>Gearlube Racing 75W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Check every 250 hours, change every 2000 hours/ 24 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2            |  |
|--------------------------------|-------------------------------------|--|
| <b>Gearlube Racing 75W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Change every 100 hours*

**TRAVEL REDUCTION UNIT**

Capacity: 3 liter (each)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2            |  |
|--------------------------------|-------------------------------------|--|
| <b>Gearlube Racing 75W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Check every 250 hours, change every 1000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*