PRODUCT RECOMMENDATION

DYNAPAC WHEELED PAVERS DF/F DF145P CUMMINS QSB-6.7C (656)

ENGINE Cummins QSB6.7C
Capacity: 16,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrisynth LSP Ultra 10W-40	**Agrisynth LSP 10W-40**	**Armado Synth LSP Ultra 10W-40**

Check every 10 hours, change every 500 hours

HYDRAULIC SYSTEM
Capacity: 175 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Perlus Biosynth 46	**Perlus H 46**	

Check every 10 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Biodegradable oil		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 2000 hours/ 24 months

CENTRAL LUBRICATION UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

DYNAPAC WHEELED PAVERS DF/F DF145P CUMMINS QSB-6.7C (656)

COOLING SYSTEM
Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Check every 10 hours, change every 2000 hours/ 24 months

AUGER TYPE I BEVEL GEAR
Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 50 hours, change every 2000 hours/ 24 months

AUGER TYPE II CHAINBOX
Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Abacot MEP 460		

Check every 250 hours, change every 1000 hours/ 12 months

AUGER TYPE II PLANETARY GEAR
Capacity: 0,5 liter (each side)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 100 hours, change every 1000 hours/ 12 months

CONVEYOR GEARBOX
Capacity: 1,5 liter (each side)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Abacot MEP Synth 220	**Abacot MEP 220**	

Check every 50 hours, change every 1000 hours/ 12 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

DYNAPAC WHEELED PAVERS DF/F DF145P CUMMINS QSB-6.7C (656)

PUMP DISTRIBUTION GEAR Capacity: 4,5 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Gearlube GL-5 80W-90**	PRODUCT RECOMMENDATION 2 **Unigear HS GL-3/GL-5 80W-90**	
Check every 50 hours, change every 1000 hours/ 12 months		

TRAVEL REDUCTION UNIT Capacity: 2,8 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Abacot MEP 220**		
Check every 50 hours, change every 1000 hours/ 12 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367