

# DYNAPAC WHEELED PAVERS DF/F F121-6W/D



## ENGINE Deutz TCD 2012 L06

USE	CLIMATE
Normal	Mediterranean

### PRODUCT RECOMMENDATION 1

**Multifleet SHPD 20W-50**

*Change every 200 hours*

USE	CLIMATE
Normal	Moderate

### PRODUCT RECOMMENDATION 1

**Agrisynth LSP 10W-40**

### PRODUCT RECOMMENDATION 2

**Kroontrak CVT 10W-40**

### PRODUCT RECOMMENDATION 3

**Agrisynth MSP 10W-40**

*Change every 200 hours*

USE	CLIMATE
Initial service	Mediterranean

### PRODUCT RECOMMENDATION 1

**Multifleet SHPD 20W-50**

*Change every 50 hours*

USE	CLIMATE
Initial service	Moderate

### PRODUCT RECOMMENDATION 1

**Agrisynth LSP 10W-40**

### PRODUCT RECOMMENDATION 2

**Kroontrak CVT 10W-40**

### PRODUCT RECOMMENDATION 3

**Agrisynth MSP 10W-40**

*Change every 50 hours*

## AUGER BEVEL GEAR

USE	CLIMATE
Normal	Moderate

### PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

### PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 1000 hours*

## DIFFERENTIAL

USE	CLIMATE
Normal	Moderate

### PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

### PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 1000 hours*

# DYNAPAC WHEELED PAVERS DF/F F121-6W/D



## HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		

*Change every 2000 hours/ 24 months*

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## AUGER GEAR NECK BEARING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## CONVEYOR GEARBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Abacot MEP Synth 220</b>	<b>Abacot MEP 220</b>	

*Change every 1000 hours*

## PUMP DISTRIBUTION GEAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.