## DYNAPAC WHEELED PAVERS DF/F F8-4W DEUTZ BF4M-1012 (678)



| <b>ENGINE</b> Deutz BF4M-1012<br>Capacity: 10 liter |                          |                               |
|---|--------------------------|-------------------------------|
| USE   |                          | CLIMATE                       |
| Normal, fuel sulfur level < 0.5 %                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1                            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| Agrisynth LSP Ultra 10W-40                          | Agrisynth LSP 10W-40     | Armado Synth LSP Ultra 10W-40 |

Check every 10 hours, change every 250 hours

| <b>DIFFERENTIAL</b> Capacity: 11,5 liter |                             |          |
|--|-----------------------------|----------|
| USE                                      |                             | CLIMATE  |
| Normal                                   |                             | Moderate |
| PRODUCT RECOMMENDATION 1                 | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                     | Unigear HS GL-3/GL-5 80W-90 |          |
| 01 1 501                                 | 10001 / 10 / 1              |          |

Check every 50 hours, change every 1000 hours/ 12 months

| HYDRAULIC SYSTEM Capacity: 80 liter (Hydraulic tank)    |                  |               |
|---|------------------|---------------|
| USE   |                  | CLIMATE       |
| Normal  |                  | Moderate      |
| PRODUCT RECOMMENDATION 1                                |                  |               |
| Perlus H 46   |                  |               |
| Check every 10 hours, change every 2000 hours/24 months |                  |               |
| USE   |                  | CLIMATE       |
| Biodegradable oil                                       |                  | Mediterranean |
| PRODUCT RECOMMENDATION 1                                |                  |               |
| Perlus Biosynth 46                                      |                  |               |
| Check every 10 hours, change every 2000                 | hours/ 24 months |               |

| HYDRAULIC BRAKE SYSTEM    |                          |          |  |
|---------------------------|--------------------------|----------|--|
| USE                       |                          | CLIMATE  |  |
| Normal                    |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |  |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4       |          |  |

## DYNAPAC WHEELED PAVERS DF/F F8-4W DEUTZ BF4M-1012 (678)



| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| COOLING SYSTEM COMBUSTION ENGINE Capacity: 12,1 liter |                          |  |
|---|--------------------------|--|
|   | CLIMATE                  |  |
|   | Moderate                 |  |
| PRODUCT RECOMMENDATION 2                              |                          |  |
| Coolant -26   |                          |  |
|   | PRODUCT RECOMMENDATION 2 |  |

Check every 10 hours, change every 2000 hours/24 months

| AUGER TYPE I BEVEL GEAR<br>Capacity: 0,6 liter (each side) |                             |          |
|--|-----------------------------|----------|
| USE  |                             | CLIMATE  |
| Normal   |                             | Moderate |
| PRODUCT RECOMMENDATION 1                                   | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                                       | Unigear HS GL-3/GL-5 80W-90 |          |
| Chack avery 50 hours, change aver                          | 1, 1000 hours/12 months     | •        |

Check every 50 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.