

DYNAPAC TOWED VIBRATORY ROLLERS

CH47


ENGINE Deutz F3L, Lister HR3-A

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SHPD 15W-40*Change every 200 hours*

USE

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SHPD 15W-40*Change every 50 hours*
ENGINE Deutz F3L-912

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SHPD 15W-40*Change every 200 hours*

USE

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SHPD 15W-40*Change every 50 hours*
GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2
DRUM

USE

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32

PRODUCT RECOMMENDATION 2

Perlus H 68*Change every 200 hours*

DYNAPAC TOWED VIBRATORY ROLLERS CH47



INJECTION PUMP & REGULATOR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		

UNIVERSAL DRIVE SHAFT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.