DYNAPAC PLANERS PL PL500/20S CUMMINS QSB4.5-C (503.173 ->)



| | CLIMATE |
|--------------------------|----------|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | |
| Multifleet SHPD 10W-40 | |
| | |

Check every 10 hours, change every 250 hours

| PLANETARY GEAR DRIVE WHEEL Capacity: 0,5 liter (each side) | | |
|---|------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Abacot MEP 220 | | |
| Check every 50 hours, change every 1000 | hours/ 12 months | |

| USE | CLIMATE |
|--------------------------|----------|
| Initial service | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Abacot MEP 220 | |
| 01 0501 | |

Change every 250 hours

| HYDRAULIC SYSTEM Capacity: 100 liter (Hydraulic tank) | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 46 | Perlus H 46 | |

Check every 10 hours, change every 1000 hours/ 12 months

| USE | | CLIMATE |
|---------------------------------------|-----------------|---------------|
| Biodegradable oil | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 46 | | |
| Chack avery 10 hours shange avery 100 | hours/12 months | · |

Check every 10 hours, change every 1000 hours/ 12 months

DYNAPAC PLANERS PL PL500/20S CUMMINS QSB4.5-C (503.173 ->)



| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| COOLING SYSTEM | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |
| <u></u> | | |

Check every 10 hours, change every 1000 hours/ 12 months

| ANGULAR GEAR Capacity: 4 liter | | |
|-----------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 50 hours, change every 500 hours

| 01 501 | | 1 |
|--------------------------|-----------------------------|----------|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Initial service | | Moderate |
| USE | | CLIMATE |

Change every 50 hours

| MILLING DRUM GEARBOX | | |
|--------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Abacot MEP 220 | | |
| | | |

Check every 50 hours, change every 1000 hours/ 12 months

| USE | CLIMATE |
|--------------------------|----------|
| Initial service | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Abacot MEP 220 | |
| 01 100 1 | 5 |

Change every 100 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

DYNAPAC PLANERS PL PL500/20S CUMMINS QSB4.5-C (503.173 ->)



information contained herein is subject to changes without notification.