DYNAPAC ROLLERS CC1200 10000332X0A000001-> (2012 AND AFTER)



| ENGINE Kubota D1703 Capacity: 7 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Check every 10 hours, change every 500 hours/ 12 months

Check every 10 hours, change every 2000 hours/ 12 months

| HYDRAULIC SYSTEM Capacity: 45 liter (Hydraulic tank) | | |
|--|--------------------|---------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 68 | | |
| Check every 10 hours, change every 2000 |) hours/ 12 months | |
| USE | | CLIMATE |
| Biodegradable oil | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 46 | | |

| GREASE POINTS/NIPPLES | | | | |
|--------------------------|--------------------------|--------------------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | | |

| COOLING SYSTEM Capacity: 5,5 liter | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |
| Check every 500 hours/ 12 months, change every 24 months | | | |

DYNAPAC ROLLERS CC1200 10000332X0A000001-> (2012 AND AFTER)



| DRUM Capacity: 4 liter | | | | |
|--|-------------------------------|---------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Mediterranean | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | | | |
| Check every 3 months/ 500 hours, chang | e every 12 months/ 2000 hours | | | |
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | | | |
| Check every 3 months/ 500 hours, chang | e every 12 months/ 2000 hours | | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.