PRODUCT RECOMMENDATION

# DYNAPAC ROLLERS CG223HF TD2011, 85110280-85110300 (2011 AND AFTER)

## ENGINE Deutz TD 2011 L04W
Capacity: 10 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agridiesel CRD+ 15W-40** | **Dieselfleet CD+ 15W-40** | **Multifleet SHPD 15W-40** |

*Check every 10 hours, change every 3 months/ 500 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agridiesel CRD+ 15W-40** | **Dieselfleet CD+ 15W-40** | **Multifleet SHPD 15W-40** |

*Change every 50 hours*

## HYDRAULIC SYSTEM
Capacity: 38 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus H 68** | | |

*Check every 10 hours, change every 2000 hours/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Biodegradable oil | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus Biosynth 46** | | |

*Check every 10 hours, change every 2000 hours/ 12 months*

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# DYNAPAC ROLLERS CG223HF TD2011, 85110280-85110300 (2011 AND AFTER)

## COOLING SYSTEM
Capacity: 9,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Coolant -38 Organic NF** | **Coolant -26** |

*Check every 500 hours/ 12 months, change every 24 months*

## DRUM DRIVE UNIT FRONT
Capacity: 1 liter (each)

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Gearlube GL-5 85W-140** | **Unigear LS GL-3/GL-5 85W-140** |

*Check every 50 hours, change every 6 months/ 1000 hours*

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** |

*Check every 50 hours, change every 6 months/ 1000 hours*

## DRUM DRIVE UNIT REAR
Capacity: 1 liter (each)

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Gearlube GL-5 85W-140** | **Unigear LS GL-3/GL-5 85W-140** |

*Check every 50 hours, change every 6 months/ 1000 hours*

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** |

*Check every 50 hours, change every 6 months/ 1000 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# DYNAPAC ROLLERS CG223HF TD2011, 85110280-85110300 (2011 AND AFTER)

| DRUM FRONT<br>Capacity: 13 liter | | |
|---|---|---|
| USE<br>Normal | | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br>**Abacot MEP HD 150** | PRODUCT RECOMMENDATION 2<br>**Abacot MEP 150** | |
| *Check every 3 months/ 500 hours, change every 12 months/ 2000 hours* | | |

| DRUM REAR<br>Capacity: 13 liter | | |
|---|---|---|
| USE<br>Normal | | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br>**Abacot MEP HD 150** | PRODUCT RECOMMENDATION 2<br>**Abacot MEP 150** | |
| *Check every 3 months/ 500 hours, change every 12 months/ 2000 hours* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367