## DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA250 /P CUMMINS QSB 4.5C (\*66021500\* ->)(2012 AND AFTER)



<b>ENGINE</b> Cummins QSB4.5C Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 3 months/ 500 hours		
USE		CLIMATE
Initial service		Moderate

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40 Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL REAR Capacity: 12 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
01 1 0501 1	0 (1 ( 1000 )	

Check every 250 hours, change every 6 months/ 1000 hours

HUB REDUCTIONS REAR Capacity: 1,85-2 liter (each hub)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 6 months/ 1000 hours

Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE

Check every 250 hours, change every 6 months/ 1000 hours

## DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA250 /P CUMMINS QSB 4.5C (\*66021500\* ->)(2012 AND AFTER)



## HYDRAULIC SYSTEM

Capacity: 75 liter (Hydraulic system including tank), Capacity: 52 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Check every 10 hours, change every 2000 hours/ 12 months		

USE		CLIMATE
Biodegradable oil		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change every 2000 hours/ 12 months		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

COOLING SYSTEM Capacity: 24 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 24 months

ARTICULATED JOINT			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

## DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA250 /P CUMMINS QSB 4.5C (\*66021500\* ->)(2012 AND AFTER)



DRUM Capacity: 15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Abacot MEP HD 150	

Check every 250 hours, change every 2000 hours/ 12 months

DRUM GEARBOX Capacity: 3 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 250 hours, change every 200	0 hours/ 12 months	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 250 hours, change eve	ery 2000 hours/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.