

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA2800 D CUMMINS T4/IIIB (10000142X0A00XXXX ->)



ENGINE Cummins QSB4.5
Capacity: 11 liter

USE

Alternative, fuel sulfur level < 0,0015 %

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrisynth MSP 10W-40****PRODUCT RECOMMENDATION 2****Agridiesel MSP 15W-40****PRODUCT RECOMMENDATION 3****Dieselfleet MSP 15W-40**

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL REAR

Capacity: 16,5 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gearlube GL-5 85W-140****PRODUCT RECOMMENDATION 2****Unigear LS GL-3/GL-5 85W-140**

Check every 250 hours, change every 1000 hours/ 24 months

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90**

Check every 250 hours, change every 1000 hours/ 24 months

DRUM CARTRIDGE

Capacity: 2,2 liter (each side)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Abacot MEP HD 150**

Check every 250 hours, change every 2000 hours/ 24 months

USE

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Abacot MEP HD 150**

Change every 50 hours

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA2800 D CUMMINS T4/IIIB (10000142X0A00XXXX ->)

**HUB REDUCTIONS**

Capacity: 1,7 liter (each hub)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 1000 hours/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

*Check every 250 hours, change every 1000 hours/ 24 months***HYDRAULIC SYSTEM**

Capacity: 80 liter (Hydraulic system including tank), Capacity: 41 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Biodegradable oil		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

*Check every 10 hours, change every 2000 hours/ 24 months***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

COOLING SYSTEM ENGINE

Capacity: 24-26,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 24 months

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA2800 D CUMMINS T4/IIIB (10000142X0A00XXXX ->)

**DRUM GEARBOX**

Capacity: 2,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Check every 250 hours, change every 1000 hours/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 1000 hours/ 24 months

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.