

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA512 D/PD CUMMINS QSB6.7C (*70X21000* ->) (2006-2011)



ENGINE Cummins QSB6.7C
Capacity: 14 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL REAR

Capacity: 12,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140

Check every 250 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 6 months/ 1000 hours

DRUM CARTRIDGE

Capacity: 2,3 liter (each side)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 150

Check every 250 hours, change every 2000 hours/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 150

Change every 50 hours

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA512 D/PD CUMMINS QSB6.7C (*70X21000* ->) (2006-2011)

**HUB REDUCTIONS REAR**

Capacity: 1,85 liter (each hub)

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140*Check every 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 250 hours, change every 6 months/ 1000 hours***HYDRAULIC SYSTEM**

Capacity: 95 liter (Hydraulic system including tank), Capacity: 52 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 68*Check every 10 hours, change every 2000 hours/ 12 months*

USE	CLIMATE
Biodegradable oil	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46*Check every 10 hours, change every 2000 hours/ 12 months***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease

PRODUCT RECOMMENDATION 2

Labora Grease

PRODUCT RECOMMENDATION

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA512 D/PD CUMMINS QSB6.7C (*70X21000* ->) (2006-2011)



COOLING SYSTEM

Capacity: 26 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 24 months

ARTICULATED JOINT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

DRUM GEARBOX

Capacity: 3,5 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.