DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA602 D/PD CUMMINS QSB6.7C (*71X21000* ->)(2006-2010)



ENGINE Cummins QSB6.7C Capacity: 14 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 3 m	onths/ 500 hours	
USE		CLIMATE
Initial service		Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40
Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL REAR Capacity: 12,5 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 6 months/ 1000 hours

		·
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE

Check every 250 hours, change every 6 months/ 1000 hours

DRUM CARTRIDGE Capacity: 2,3 liter (each side)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Abacot MEP HD 150	

Check every 250 hours, change every 2000 hours/ 12 months

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Abacot MEP HD 150	
Change every 50 hours	·

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA602 D/PD CUMMINS QSB6.7C (*71X21000* ->)(2006-2010)



HUB REDUCTIONS REAR Capacity: 1,85 liter (each hub)		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 250 hours change every 6 m	onths/1000 hours	

Check every 250 hours, change every 6 months/ 1000 hours

	r HS GL-3/GL-5 80W-90
use	CLIMATE
Normal	Moderate

Check every 250 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM Capacity: 95 liter (Hydraulic system including tank), Capacity: 52 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Check every 10 hours, change every 2000	hours/ 12 months	
USE		CLIMATE
Biodegradable oil		Mediterranean

PRODUCT RECOMMENDATION 1

Check every 10 hours, change every 2000 hours/ 12 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA602 D/PD CUMMINS QSB6.7C (*71X21000* ->) (2006-2010)



COOLING SYSTEM Capacity: 26 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
04	·		

Change every 24 months

ARTICULATED JOINT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

DRUM GEARBOX Capacity: 3,5 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 250 hours, change every		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.