

PRODUCT RECOMMENDATION

DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC1100C KUBOTA D1703 (10000331X0A009254 ->)



ENGINE Kubota D1703-M
Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours

HYDRAULIC SYSTEM
Capacity: 45 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 2000 hours/ 12 months

USE	CLIMATE
Biodegradable oil	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 2000 hours/ 12 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

COOLING SYSTEM
Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours/ 24 months

PRODUCT RECOMMENDATION

DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC1100C KUBOTA D1703 (10000331X0A009254 ->)



DRUM

Capacity: 4 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.