DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC1200C KUBOTA D1703 (10000333X0A000001 ->)



ENGINE Kubota D1703-M Capacity: 7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
011	0501		

Check every 10 hours, change every 250 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 50 hours

HYDRAULIC SYSTEM Capacity: 45 liter (Hydraulic tank)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 2000 hours/ 12 months

USE	CLIMATE
Biodegradable oil	Mediterranean
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	

Check every 10 hours, change every 2000 hours/ 12 months

	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2		
Labora Grease		
		PRODUCT RECOMMENDATION 2

DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC1200C KUBOTA D1703 (10000333X0A000001 ->)



COOLING SYSTEM Capacity: 5,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Chack avery 10 hours, change aver	2000 hours/24 months		

Check every 10 hours, change every 2000 hours/24 months

DRUM Capacity: 4 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 3 months/500 hours, change every 12 months/2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.