

# DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC121 DEUTZ F2L-511 (1988-1992)

**ENGINE** Deutz F2L-511

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40***Change every 200 hours*

USE	CLIMATE
Initial service	Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40***Change every 50 hours***HYDRAULIC SYSTEM**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Perlus H 68***Change every 2000 hours/ 12 months***AIR CLEANER OIL BATH**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40****ARTICULATED JOINT BEARINGS**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Labora Grease**

## PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

## PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2****CONTROLS HINGES JOINTS**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Labora Grease**

## PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

## PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

# DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC121 DEUTZ F2L-511 (1988-1992)



## DRUM FRONT

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	
<i>Change every 200 hours</i>		

## DRUM REAR

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	
<i>Change every 200 hours</i>		

## STEERING CYLINDER MOUNTINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.