DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC142C DEUTZ D2011-L03I (10000310X0A000001->)



Multifleet SHPD 15W-40

ENGINE Deutz D m2011 L03i Capacity: 6 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Check every 10 hours, change every 3 months/ 500 hours				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		

Dieselfleet CD+ 15W-40

Change every 50 hours

Agridiesel CRD+ 15W-40

HYDRAULIC SYSTEM Capacity: 40 liter (Hydraulic tank)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Perlus H 68				
Check every 10 hours, change every 2000 hours/ 12 months				
USE		CLIMATE		
Biodegradable oil		Mediterranean		
PRODUCT RECOMMENDATION 1				
Perlus Biosynth 46				

Check every 10 hours, change every 2000 hours/ 12 months

	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2		
Labora Grease		
		PRODUCT RECOMMENDATION 2

DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC142C DEUTZ D2011-L03I (10000310X0A000001->)



DRUM Capacity: 6 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140			
Check every 3 months/ 500 hours, change every 12 months/ 2000 hours				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90			
Check every 3 months/ 500 hours, change every 12 months/ 2000 hours				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.