EUROCOMACH TRACKED EXCAVATORS ES 500ZT KUBOTA V2403-M (S/N CI 00310 -



>) (2004 AND AFTER)

ENGINE Kubota V2403-M Capacity: 9,5 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 250 hours		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 250 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Asyntho 5W-30	Armado Synth 5W-30
Change every 250 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
Change every 250 hours JSE		OLIMATE.
Initial service		climate Tropical
iritiai scrvicc		
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE		CLIMATE
Multifleet SCD 30 Change every 50 hours USE		сымате Mediterranean
Multifleet SCD 30 Change every 50 hours JSE Initial service		
Multifleet SCD 30 Change every 50 hours USE Initial Service PRODUCT RECOMMENDATION 1		
Multifleet SCD 30 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20		
Multifleet SCD 30		
Multifleet SCD 30 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours		Mediterranean
Multifleet SCD 30 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours USE	PRODUCT RECOMMENDATION 2	Mediterranean

EUROCOMACH TRACKED EXCAVATORS ES 500ZT KUBOTA V2403-M (S/N CI 00310 -



>) (2004 AND AFTER)

use Initial service	CLIMATE Arctic
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 50 hours	

HYDRAULIC SYSTEM Capacity: 60 liter (Hydraulic system including tank), Capacity: 20 liter (Hydraulic tank) USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 **Perlus Biosynth 46** Perlus H 46 Change every 1000 hours CLIMATE Initial service Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Perlus Biosynth 46 Perlus H 46 Change every 250 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 24 months		

Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
	Moderate
	CLIMATE
	PRODUCT RECOMMENDATION 2

Dollegoorweg 15

7602 EC Almelo

EUROCOMACH TRACKED EXCAVATORS ES 500ZT KUBOTA V2403-M (S/N CI 00310 -



>) (2004 AND AFTER)

TRAVEL REDUCTION UNIT Capacity: 1,3 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1000 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 250 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.