GEHL SKID STEER LOADERS R/SL/V SL-1620 ISUZU 3KC1 (1985-1992)



ENGINE Isuzu 3KC1		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	HDX 40	
Change every 100 hours		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
HDX 30		
Change every 100 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Change every 100 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Change every 100 hours		

HYDRAULIC SYSTEM HYDROSTATIC DRIVE		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Change every 500 hours/ 12 months		

use CLIMATE Normal Moderate	RECOMMENDATION 3	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 1
			use Normal
GREASE POINTS/NIPPLES			GREASE POINTS/NIPPLES

GEHL SKID STEER LOADERS R/SL/V SL-1620 ISUZU 3KC1 (1985-1992)



DRIVE CHAIN CASE	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	
Change every 500 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.