

# GEHL SKID STEER LOADERS R/SL/V SL-1640E YANMAR 3TNV82 (2010 AND AFTER)



**ENGINE** Yanmar 3TNV82  
Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth LSP 10W-40</b>	<b>Agridiesel CRD+ 15W-40</b>

*Change every 500 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth LSP 10W-40</b>	<b>Agridiesel CRD+ 15W-40</b>

*Change every 50 hours*

## HYDRAULIC SYSTEM

Capacity: 30 liter (Hydraulic system including tank), Capacity: 27,2 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus HCD 46</b>		

*Change every 1000 hours/ 12 months*

## COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 500 hours/ 12 months*

# GEHL SKID STEER LOADERS R/SL/V SL-1640E YANMAR 3TNV82 (2010 AND AFTER)

**DRIVE CHAIN CASE**

Capacity: 7,6 liter (each side)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Check every 250 hours, change every 1000 hours/ 12 months*

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 50 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*