GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3384 RT DEUTZ F3L 2011F (40833 -) (2008 AND AFTER)



ENGINE Deutz F3L-2011 Capacity: 8 liter, Capacity: 6 liter (Cha	nge capacity)	
USE		CLIMATE
Preferred, high load		Moderate
PRODUCT RECOMMENDATION 1		
Agrisynth LSP 10W-40		
Check every 10 hours, change every	500 hours/ 12 months	
USE		CLIMATE
Preferred, normal load		Moderate
PRODUCT RECOMMENDATION 1		
Agrisynth LSP 10W-40		
Check every 8 hours, change every 12	2 months/ 1000 hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Check every 8 hours, change every 12	2 months/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40
Check every 8 hours, change every 12	2 months/ 1000 hours	
USE		CLIMATE
Normal, high load		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Check every 10 hours, change every	500 hours/ 12 months	
USE		CLIMATE
Normal, high load		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40
Check every 10 hours, change every	500 hours/ 12 months	
USE		CLIMATE
A1(() () () () () () ()	load	Mediterranean
Alternative (acceptable), normal		
Alternative (acceptable), normal product recommendation 1		

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3384 RT DEUTZ F3L 2011F (40833 -) (2008 AND AFTER)



use Alternative (acceptable), normal	load	сымате Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Helar 0W-40	Agridiesel CRD+ 15W-40
Check every 8 hours, change every 1	2 months/ 1000 hours	
USE		CLIMATE
Alternative (acceptable), high loa	ad	Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Check every 10 hours, change every	500 hours/ 12 months	·
USE		CLIMATE
Alternative (acceptable), high loa	ad	Moderate
PPODLICT PECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Helar 0W-40	Agridiesel CRD+ 15W-40
Check every 10 hours, change every 500	hours/ 12 months	

HUB REDUCTIONS Capacity: 0,77 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/ 12 months

outriggers) USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Check every 250 hours, change ev	ery 2000 hours/ 24 months	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 32	Perlus AF 46

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3384 RT DEUTZ F3L 2011F (40833 -) (2008 AND AFTER)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.