GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3390 RT DEUTZ D2011 L03I (47229 -) (2008 AND AFTER)



ENGINE Deutz D 2011 L03i		
Capacity: 9 liter, Capacity: 7 liter (Change	capacity)	
USE		CLIMATE
Preferred, high load		Moderate
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40		
Check every 10 hours, change every 500 l	nours/ 12 months	
USE		CLIMATE
Preferred, normal load		Moderate
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40		
Check every 8 hours, change every 12 mo	nths/ 1000 hours	1
use Normal		climate Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50		
Check every 8 hours, change every 12 mo	nths/ 1000 hours	
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 2 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40
Check every 8 hours, change every 12 mo	nths/ 1000 hours	
use Normal, high load		climate Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50		
Check every 10 hours, change every 500 l	hours/ 12 months	1
use Normal, high load		climate Moderate
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 2 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40
Check every 10 hours, change every 500 l	hours/ 12 months	1
use Alternative (acceptable), normal load	I	сымате Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50		

Check every 8 hours, change every 12 months/ 1000 hours

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3390 RT DEUTZ D2011 L03I (47229 -) (2008 AND AFTER)



USE		CLIMATE
Alternative (acceptable), normal load	l	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Helar 0W-40	Agridiesel CRD+ 15W-40
Check every 8 hours, change every 12 mo	nths/ 1000 hours	
USE		CLIMATE
Alternative (acceptable), high load		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Check every 10 hours, change every 500 h	nours/ 12 months	
USE		CLIMATE
Alternative (acceptable), high load		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Helar 0W-40	Agridiesel CRD+ 15W-40

Check every 10 hours, change every 500 hours/ 12 months

HUB REDUCTIONS Capacity: 0,77 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 114 liter (Hydraulic tank), Capacity: 142 liter (System, with outriggers), Capacity: 129,6 liter (System, without outriggers)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 250 hours, change every 2000 hours/ 24 months

Perlus H 46	Perlus H 32	Perlus AF 46
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Alternative (acceptable)		Moderate
USE		CLIMATE

Check every 250 hours, change every 2000 hours/ 24 months

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3390 RT DEUTZ D2011 L03I (47229 -) (2008 AND AFTER)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.