GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-4390 RT FORD LRG-425EFI (42686 -) (2008 AND AFTER)



| ENGINE Ford LRG-425 EFI Capacity: 4,3 liter | | |
|---|-------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Synfleet SHPD 10W-40 | | |
| Check every 10 hours, change every 200 | hours | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Asyntho 5W-30 | | |
| Check every 10 hours, change every 200 | hours | |

| HUB REDUCTIONS Capacity: 0,77 liter (each hub) | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Check every 250 hours, change every 100 | 00 hours/ 12 months | |
| USE | | CLIMATE |
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |

| USE | | CLIWATE |
|--------------------------|-----------------------------|----------|
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 150 hours | | <u> </u> |

| HYDRAULIC SYSTEM Capacity: 114 liter (Hydraulic tank), Capacity: 144,8 liter (System, with outriggers), Capacity: 132,5 liter (System, without outriggers) | | | |
|--|---------------------------|----------|--|
| use Normal | | CLIMATE | |
| | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| SP Matic 2032 | ATF Almirol | | |
| Check every 250 hours, change ev | very 2000 hours/24 months | ' | |

| Check every 250 hours, change ev | ery 2000 hours/ 24 months | • |
|----------------------------------|------------------------------|--------------------------|
| Perlus H 46 | Perlus H 32 | Perlus AF 46 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Alternative (acceptable) | | Moderate |
| USE | | CLIMATE |
| Check every 200 hours, change ev | ory 2000 Hourd, 2 Fillionale | |

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-4390 RT FORD LRG-425EFI (42686 -) (2008 AND AFTER)



| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| COOLING SYSTEM Capacity: 10,9 liter | | | |
|-------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |
| Check every 10 hours, change every | v 800 hours | • | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.