

# GENIE TELEHANDLERS GTH/AGRI GTH-1056 JOHN DEERE, GTH1006A-8418 - GTH1007A-11442



**ENGINE** John Deere 4045 TF275  
Capacity: 13,2 liter

| USE      | CLIMATE  |
|----------|----------|
| Extended | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3     |
|-----------------------------|-----------------------------|------------------------------|
| <b>Agrisynth LSP 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3     |
|-----------------------------|-----------------------------|------------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

*Check every 10 hours, change every 6 months/ 250 hours*

**DIFFERENTIAL FRONT** Dana 213  
Capacity: 14,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

**DIFFERENTIAL REAR** Dana 213  
Capacity: 14,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

**HUB REDUCTIONS FRONT** Dana 213  
Capacity: 1,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

# GENIE TELEHANDLERS GTH/AGRI GTH-1056 JOHN DEERE, GTH1006A-8418 - GTH1007A-11442

**HUB REDUCTIONS REAR** Dana 213

Capacity: 1,9 liter

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gearlube LS 80W-90</b> |  |          |

**TRANSMISSION** Dana T20000 3/3

Capacity: 18,9 liter

| USE                         |                             | CLIMATE                  |
|-----------------------------|-----------------------------|--------------------------|
| Normal                      |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

**HYDRAULIC SYSTEM**

Capacity: 181,7 liter (Hydraulic tank), Capacity: 249,8 liter (System)

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |          |

**COOLING SYSTEM**

Capacity: 18,9 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.