

# GENIE TELEHANDLERS GTH/AGRI GTH-3713 SX (11321 -> 15943) - PERKINS 1104C-44



**ENGINE** Perkins 1104C-44  
Capacity: 11,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Check every 8 hours, change every 12 months/ 500 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Armado Synth 5W-30</b>

*Check every 8 hours, change every 12 months/ 500 hours*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Check every 8 hours, change every 12 months/ 250 hours*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Armado Synth 5W-30</b>

*Check every 8 hours, change every 12 months/ 250 hours*

**DIFFERENTIAL FRONT**  
Capacity: 8,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 250 hours, change every 1000 hours/ 12 months*

**DIFFERENTIAL REAR**  
Capacity: 8,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 250 hours, change every 1000 hours/ 12 months*

# GENIE TELEHANDLERS GTH/AGRI GTH-3713 SX (11321 -> 15943) - PERKINS 1104C-44

**GEARBOX**

Capacity: 1,5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Check every 250 hours, change every 1000 hours/ 12 months***HUB REDUCTIONS FRONT**

Capacity: 0,75 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Check every 8 hours, change every 12 months/ 1000 hours***HUB REDUCTIONS REAR**

Capacity: 0,75 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Check every 8 hours, change every 12 months/ 1000 hours*

# GENIE TELEHANDLERS GTH/AGRI GTH-3713 SX (11321 -> 15943) - PERKINS 1104C-44



## HYDRAULIC SYSTEM

Capacity: 150 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 68</b>	<b>Perlus AF 68</b>	

*Check every 8 hours, change every 12 months/ 1000 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus AF 46</b>	

*Check every 8 hours, change every 12 months/ 1000 hours*

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 22</b>	<b>Perlus AF 32</b>	

*Check every 8 hours, change every 12 months/ 1000 hours*

## COOLING SYSTEM

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 8 hours, change every 24 months/ 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*