GENIE TELEHANDLERS GTH/AGRI GTH-844 JOHN DEERE, GTH0808B-6956 ->



ENGINE John Deere 4045 TF270 Capacity: 13,2 liter		
USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Check every 10 hours, change every 500 hours/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Check every 10 hours, change every 6 months/ 250 hours

DIFFERENTIAL FRONT Dana 212 Capacity: 8,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

DIFFERENTIAL REAR Dana 212 Capacity: 5,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

HUB REDUCTIONS FRONT Dana 212 Capacity: 0,9 liter	
use Normal	сымате Moderate
PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90	

GENIE TELEHANDLERS GTH/AGRI GTH-844 JOHN DEERE, GTH0808B-6956 ->



HUB REDUCTIONS REAR Dana 212 Capacity: 0,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

TRANSMISSION Dana T12000 3/3 Capacity: 12,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

HYDRAULIC SYSTEM Capacity: 129 liter (Hydraulic tank), Capacity: 189 liter (System)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

COOLING SYSTEM Capacity: 9,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours, change every 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.