

# GENIE TELESCOPIC BOOMS, SELF PROPELLED S-... S-60 TRAX PERKINS 404- 22 (S60TX10-21001->)(2012 AND AFTER)



**ENGINE** Perkins 404-22  
Capacity: 8,8 liter

USE  
Normal

CLIMATE  
Mediterranean

PRODUCT RECOMMENDATION 1  
**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2  
**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 3  
**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 500 hours*

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 2  
**Multifleet SHPD 10W-40**

*Check every 10 hours, change every 500 hours*

## HUB REDUCTIONS

Capacity: 0,6 liter (each hub)

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2  
**Unigear HS GL-3/GL-5 80W-90**

*Check every 1 months/ 250 hours, change every 1000 hours/ 12 months*

USE  
Initial service

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2  
**Unigear HS GL-3/GL-5 80W-90**

*Change every 150 hours*

## HYDRAULIC SYSTEM

Capacity: 208 liter (Complete), Capacity: 170 liter (Hydraulic tank)

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**SP Matic 2032**

PRODUCT RECOMMENDATION 2  
**ATF Almirol**

*Check every 10 hours, change every 2000 hours/ 24 months*

USE  
Biodegradable oil

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Perlus Biosynth 46**

PRODUCT RECOMMENDATION 2  
**Perlus Biosynth 32**

*Check every 10 hours, change every 2000 hours/ 24 months*

# GENIE TELESCOPIC BOOMS, SELF PROPELLED S-... S-60 TRAX PERKINS 404- 22 (S60TX10-21001->)(2012 AND AFTER)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## COOLING SYSTEM

Capacity: 7,3 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 10 hours

## TURNTABLE ROTATION GEAR

Capacity: 1,2-1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.