GIANT ARTICULATED LOADERS D202S KUBOTA D902 (2007 AND AFTER)



ENGINE Kubota D902 Capacity: 3,8 liter					
use Normal		climate Moderate			
			PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40			
Check every 8 hours, change every 200) hours				
USE		CLIMATE			
Initial service		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40			

HYDRAULIC SYSTEM Capacity: 25 liter				
use Normal		CLIMATE		
		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Perlus Biosynth 46	Perlus H 46	Perlus Biosynth 32		
Chook avery 50 hours, change ave	1000 hours			

Check every 50 hours, change every 1000 hours

Check every 8 hours, change every 50 hours

USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Perlus Biosynth 46	Perlus H 46	Perlus Biosynth 32	
Change every 50 hours		'	

GREASE POINTS/NIPPLES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

GIANT ARTICULATED LOADERS D202S KUBOTA D902 (2007 AND AFTER)



COOLING SYSTEM Capacity: 3,35 liter		
USE		CLIMATE
Normal		All climates
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 8 hours, change every	24 months	

Check every 8 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.