GRADALL MATERIAL HANDLERS 534C-10 S/N 0266107 - 0266139



ENGINE Capacity: 11,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT Capacity: 15,6 liter			
use Normal		сцімате Moderate	
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30	
Check every 250 hours, change ever	4 6 months / 1000 hours		

Check every 250 hours, change every 6 months/ 1000 hours

HUB REDUCTIONS REAR Capacity: 1,4 liter			
use Normal		сымате Moderate	
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30	

Check every 250 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM Capacity: 177,9 liter		
use Normal		CLIMATE
		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 500 hours/ 3 months, ch	range every 12 months/ 1500 hours	'

COOLING SYSTEM Capacity: 22,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

GRADALL MATERIAL HANDLERS 534C-10 S/N 0266107 - 0266139



information contained herein is subject to changes without notification.