## GRADALL CRAWLER EXCAVATORS XL3210 III DETROIT DIESEL OM904 T3 (3210000009 ->)



ENGINE Detroit Diesel (MB) OM904 Capacity: 16 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SHPD 15W-40	

Check every 10 hours, change every 600 hours

CRAWLER PLANETARY GEARS Capacity: 6 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube LS 80W-90
Check every 50 hours, change every 1500	) hours	

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube LS 80W-90

Change every 250 hours/ 1 months

SWING TRANSMISSION			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		
Check every 50 hours, change eve	ry 1500 hours		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 250 hours/ 1 months

## GRADALL CRAWLER EXCAVATORS XL3210 III DETROIT DIESEL OM904 T3 (3210000009 ->)



HYDRAULIC SYSTEM Capacity: 246 liter (Hydraulic system including tank), Capacity: 208 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 10 hours, change every 750 hours

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
HT Q9 High Grade Grease	Labora Grease		

COOLING SYSTEM Capacity: 21,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 1500 hours

SWING BULL GEAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

TILT BULL GEAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Compound OGL	Compound OGL EP 0/1	
Change even 100 hours	· · ·	

Change every 100 hours

## GRADALL CRAWLER EXCAVATORS XL3210 III DETROIT DIESEL OM904 T3 (3210000009 ->)



TILT GEARBOX Capacity: 0,9-1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

<b>TRACK IDLER</b> Capacity: 0,34-0,52 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.