

GROVE CRANES MOBILE CRANES YB5515

GM (2008 AND AFTER)

**ENGINE GM**

Capacity: 5,2 liter, Filter capacity: 0,9 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

HDX 40*Check every 10 hours, change every 1 months/ 250 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

HDX 20W-50

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

PRODUCT RECOMMENDATION 3

HDX 30*Check every 10 hours, change every 1 months/ 250 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30*Check every 10 hours, change every 1 months/ 250 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

HDX 10W*Check every 10 hours, change every 1 months/ 250 hours***DIFFERENTIAL FRONT**

Capacity: 23 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30*Check every 3 months/ 500 hours, change every 6 months/ 1000 hours***HUB REDUCTIONS FRONT**

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30*Check every 3 months/ 500 hours, change every 6 months/ 1000 hours*

GROVE CRANES MOBILE CRANES YB5515

GM (2008 AND AFTER)



TRANSMISSION MANUAL ITL 4/4

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-F (Ford)		
Check every 10 hours, change every 6 months/ 1000 hours		

HYDRAULIC SYSTEM

Capacity: 89 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 10 hours, change every 6 months/ 1000 hours		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours		

COOLING SYSTEM

Capacity: 21,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours, change every 2000 hours/ 12 months		

HOIST REDUCTION UNIT Tulsa

Capacity: 1,4-1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1000 hours/ 6 months		

GROVE CRANES MOBILE CRANES YB5515

GM (2008 AND AFTER)

**HOIST WINCH BRAKE** Tulsa

Capacity: 0,2-0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20**SWING REDUCTION UNIT** Braden

Capacity: 0,95 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP 460*Change every 1000 hours/ 6 months***SWING REDUCTION UNIT** Tulsa

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 3 months/ 500 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.