

# HAKO/MULTICAR CITYMASTER

## CITYMASTER 300 (1125.11/12/13)

### LOMBARDINI LDW1003-B4

**ENGINE LDW 1003**

Capacity: 2,4 liter, Filter capacity: 0,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Asyntho 5W-30</b>

*Check every 8 hours, change every 12 months/ 250 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Asyntho 5W-30</b>

*Change every 50 hours***HYDRAULIC SYSTEM**

Capacity: 32 liter (Service fill), Capacity: 35 liter (Total system volume)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus AF 46</b>	

*Check every 8 hours, change every 12 months/ 500 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Check every 8 hours, change every 12 months/ 500 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 22</b>	<b>Perlus AF 32</b>	

*Check every 8 hours, change every 12 months/ 500 hours***COOLING SYSTEM**

Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15</b>	<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>

*Check every 8 hours, change every 24 months/ 1000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

**HAKO/MULTICAR CITYMASTER  
CITYMASTER 300 (1125.11/12/13)  
LOMBARDINI LDW1003-B4**



*advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*