

HAKO/MULTICAR MULTICAR M31T (4X2)

IVECO F1CE3481R (EURO 5)

(WMU2M31E5DW000001 ->)



ENGINE Iveco F1CE3481R
Capacity: 5,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR

Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 30000 km/ 24 months/ 600 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 2500 km/ 50 hours

TRANSMISSION MANUAL W 32 S5/Nh7 5/1

Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 30000 km/ 600 hours, change every 60000 km/ 24 months/ 1200 hours

TRANSMISSION MANUAL W32 S5 (4130) 5/1

Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 30000 km/ 600 hours, change every 60000 km/ 24 months/ 1200 hours

HAKO/MULTICAR MULTICAR M31T (4X2)

IVECO F1CE3481R (EURO 5)

(WMU2M31E5DW000001 ->)

**HYDRAULIC SYSTEM**

Capacity: 8 liter (Hydraulic tank. For electric tilt hydraulics EHK), Capacity: 70 liter (Hydraulic tank. Stationary hydraulics (Variant 02)), Capacity: 70 liter (Hydraulic tank. To operate all front-end and chassis attachments (Variant 07))

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Perlus Biosynth 46	Perlus H 46

Check every 50 hours, change every 24 months/ 30000 km

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Perlus Biosynth 32	Perlus H 32

Check every 50 hours, change every 24 months/ 30000 km

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
Perlus H 22	

Check every 50 hours, change every 24 months/ 30000 km

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	

Check every 50 hours, change every 24 months/ 30000 km

HYDRAULIC BRAKE SYSTEM

Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Drauliquid DOT 5.1	

Check every 50 hours, change every 60000 km/ 24 months/ 1200 hours

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Drauliquid DOT 5.1	

Check every 50 hours, change every 60000 km/ 24 months/ 1200 hours

HAKO/MULTICAR MULTICAR M31T (4X2)

IVECO F1CE3481R (EURO 5)

(WMU2M31E5DW000001 ->)



GREASE POINTS/NIPPLES CARDAN SHAFTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Change every 50 hours

GREASE POINTS/NIPPLES GENERAL

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

Change every 50 hours

COOLING SYSTEM

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Check every 50 hours, change every 60000 km/ 24 months/ 1200 hours

HYDRAULIC SYSTEM STEERING

Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	

Check every 50 hours, change every 60000 km/ 24 months/ 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.