PRODUCT RECOMMENDATION

HAMM DOUBLE DRUM COMPACTORS DV/HD DV 90 TO DEUTZ BF4M2012 (H1660001 ->)

ENGINE Deutz BF4M-2012
Capacity: 9,5 liter (Service fill)

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 50 hours		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	**Kroontrak CVT 10W-40**	**Agrisynth MSP 10W-40**
Change every 50 hours		

USE		CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 500 hours		

USE		CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	**Kroontrak CVT 10W-40**	**Agrisynth MSP 10W-40**
Change every 500 hours		

HYDRAULIC SYSTEM
Capacity: 45 liter (Hydraulic tank)

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 68	**Perlus AF 68**	**Perlus AF 100**
Change every 2000 hours		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	**Perlus AF 46**	
Change every 2000 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

HAMM DOUBLE DRUM COMPACTORS DV/HD DV 90 TO DEUTZ BF4M2012 (H1660001 ->)

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 2000 hours		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 22	**Perlus AF 32**	
Change every 2000 hours		

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Change every 2000 hours		

USE		CLIMATE
Biodegradable oil		Cold
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 32		
Change every 2000 hours		

COOLING SYSTEM
Capacity: 16 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367