HAMM DOUBLE DRUM COMPACTORS DV/HD HD 10K DEUTZ F2L 2011 (H1393612 -



>)

JSE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 50 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40
Change every 50 hours		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %	6, ambient temperature > -10°C	Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 1000 hours		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40
Agrisynth LSP 10W-40	Trioditian OVI 1011 40	5 ,

Capacity: 35 liter			
USE		CLIMATE	
Normal		Tropical	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Perlus H 68	Perlus AF 68	Perlus AF 100	
Change every 2000 hours	·		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus H 46	Perlus AF 46		
Change every 2000 hours	,		

PRODUCT RECOMMENDATION

HAMM DOUBLE DRUM COMPACTORS DV/HD HD 10K DEUTZ F2L 2011 (H1393612 -



>)

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 22	Perlus AF 32	
Change every 2000 hours		
USE		CLIMATE
use Biodegradable oil		climate Moderate
Biodegradable oil		
Biodegradable oil PRODUCT RECOMMENDATION 1		
Biodegradable oil PRODUCT RECOMMENDATION 1 Perlus Biosynth 46		
Biodegradable oil PRODUCT RECOMMENDATION 1 Perlus Biosynth 46 Change every 2000 hours		Moderate
Biodegradable oil PRODUCT RECOMMENDATION 1 Perlus Biosynth 46 Change every 2000 hours USE		Moderate
Biodegradable oil PRODUCT RECOMMENDATION 1 Perlus Biosynth 46 Change every 2000 hours USE Biodegradable oil		Moderate

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.