HAMM DOUBLE DRUM COMPACTORS DV/HD HD 12 VT HATZ 4W35 (H1710001 ->)



ENGINE Hatz 4W35 Capacity: 5 liter (Service fill)			
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1			
Multifleet SHPD 20W-50			
Change every 50 hours	·		
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	
Change every 50 hours		·	
USE		CLIMATE	
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Mediterranean	
PRODUCT RECOMMENDATION 1			
Multifleet SHPD 20W-50			
Change every 250 hours		·	
USE		CLIMATE	
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	
Change every 250 hours			

Capacity: 28 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 68	Perlus AF 68	Perlus AF 100
Change every 2000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
Change every 2000 hours		·

HYDRAULIC SYSTEM

HAMM DOUBLE DRUM COMPACTORS DV/HD HD 12 VT HATZ 4W35 (H1710001 ->)



USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 22	Perlus AF 32	
Change every 2000 hours		
USE		CLIMATE
use Biodegradable oil		CLIMATE Moderate
Biodegradable oil		
Biodegradable oil PRODUCT RECOMMENDATION 1		
Biodegradable oil PRODUCT RECOMMENDATION 1 Perlus Biosynth 46		
Biodegradable oil PRODUCT RECOMMENDATION 1 Perlus Biosynth 46 Change every 2000 hours		Moderate
Biodegradable oil PRODUCT RECOMMENDATION 1 Perlus Biosynth 46 Change every 2000 hours USE		Moderate
Biodegradable oil PRODUCT RECOMMENDATION 1 Perlus Biosynth 46 Change every 2000 hours USE Biodegradable oil		Moderate

COOLING SYSTEM Capacity: 7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.