## HAMM DOUBLE DRUM COMPACTORS DV/HD HD+ 120 VV-HV DEUTZ TCD2012 L04 2V (H1840021 -> 1840053)



USE		CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 500 hours	·	
USE		CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Change every 500 hours		

USE		CLIMATE	
Normal		Tropical	
PRODUCT RECOMMENDATION 1			
Perlus H 68			
Change every 2000 hours			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 46	Perlus H 46		
Change every 2000 hours			
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 32	Perlus H 32		
Change every 2000 hours			
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1			
Perlus H 22			

PRODUCT RECOMMENDATION

## HAMM DOUBLE DRUM COMPACTORS DV/HD HD+ 120 VV-HV DEUTZ TCD2012 L04 2V (H1840021 -> 1840053)



USE		CLIMATE			
Biodegradable oil		Moderate			
PRODUCT RECOMMENDATION 1					
Perlus Biosynth 46					
Change every 2000 hours					
USE		CLIMATE			
Biodegradable oil		Cold			
PRODUCT RECOMMENDATION 1					
Perlus Biosynth 32					
Change every 2000 hours					

## COOLING SYSTEM

Capacity: 16 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## VIBRATOR Capacity: 10,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.