HAMM DOUBLE DRUM COMPACTORS DV/HD HD 13 VT HATZ 4W35T (H1720001 ->)



| ENGINE Hatz 4W35T Capacity: 5 liter (Service fill) | | |
|---|-------------------------------|--------------------------|
| USE | | CLIMATE |
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SHPD 20W-50 | | |
| Change every 50 hours | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP 10W-40 | Kroontrak CVT 10W-40 | Agrisynth MSP 10W-40 |
| Change every 50 hours | | |
| USE | | CLIMATE |
| Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SHPD 20W-50 | | |
| Change every 250 hours | | |
| USE | | CLIMATE |
| Normal, fuel sulfur level <0,5 % | , ambient temperature > -10°C | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP 10W-40 | Kroontrak CVT 10W-40 | Agrisynth MSP 10W-40 |
| Change every 250 hours | | |
| | | |
| HYDRAULIC SYSTEM | | |
| Capacity: 55 liter (Hydraulic tank) | | |
| USE Normal | | CLIMATE |
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 Perlus H 68 | | |
| Felius II 00 | | |

PRODUCT RECOMMENDATION 2

Perlus H 46

Change every 2000 hours

PRODUCT RECOMMENDATION 1

Change every 2000 hours

Perlus Biosynth 46

USE

Normal

CLIMATE

Moderate

HAMM DOUBLE DRUM COMPACTORS DV/HD HD 13 VT HATZ 4W35T (H1720001 ->)



| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 32 | Perlus H 32 | |
| Change every 2000 hours | | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 22 | | |
| Change every 2000 hours | | |
| USE | | CLIMATE |
| Biodegradable oil | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 46 | | |
| Change every 2000 hours | | |
| USE | | CLIMATE |
| Biodegradable oil | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 32 | | |
| Change every 2000 hours | | |

COOLING SYSTEM Capacity: 7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.