HAMM DOUBLE DRUM COMPACTORS DV/HD HD 70 DEUTZ TD2011 L04W TIER 3



(H1870614 ->) (TILL 2012)

ENGINE Deutz TD 2011 L04W		
Capacity: 10 liter (Service fill)		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 500 hours		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40
Change every 500 hours		
HYDRAULIC SYSTEM		
Capacity: 45 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Change every 2000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Change every 2000 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 32	Perlus H 32	
Change every 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 22		

Change every 2000 hours

PRODUCT RECOMMENDATION

HAMM DOUBLE DRUM COMPACTORS DV/HD HD 70 DEUTZ TD2011 L04W TIER 3 (H1870614 ->) (TILL 2012)



DIODECT RECOMMENDATION 1
Perlus Biosynth 46

Change every 2000 hours

USE
Biodegradable oil

PRODUCT RECOMMENDATION 1
Change every 2000 hours

Climate
Cold

Cold

PRODUCT RECOMMENDATION 1
PRODUCT RECOMMENDATION 1
Perlus Biosynth 32

COOLING SYSTEM

Change every 2000 hours

Capacity: 11 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

VIBRATOR

Capacity: 7 liter (each drum)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.