HAMM DOUBLE DRUM COMPACTORS DV/HD HD+ 90 VV-HV DEUTZ TCD2012 L04 2V TIER 3 (H1850001 ->)



ENGINE Deutz TCD 2012 L04 2V Capacity: 11,5 liter (Service fill)		
USE Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		сымате Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50		
Change every 500 hours	•	·
USE Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		сымате Moderate
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 2 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40
Change every 500 hours		

Capacity: 40 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Change every 2000 hours		
JSE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Change every 2000 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 32	Perlus H 32	
Change every 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 22		

PRODUCT RECOMMENDATION

HAMM DOUBLE DRUM COMPACTORS DV/HD HD+ 90 VV-HV DEUTZ TCD2012 L04 2V TIER 3 (H1850001 ->)



USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Change every 2000 hours		
USE	(CLIMATE
use Biodegradable oil		climate Cold
Biodegradable oil		

COOLING SYSTEM

Capacity: 16 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

VIBRATOR Capacity: 6,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.