HAMM DOUBLE DRUM COMPACTORS DV/HD HD O70V DEUTZ BF4M1011F (H1520018 ->)



ENGINE Deutz BF4M-1011F Capacity: 10 liter (Service fill)		
USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Change every 50 hours		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30
Change every 50 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 10W-40		
Change every 50 hours		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %, amb	pient temperature > -10°C	Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Change every 500 hours		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %, amb	pient temperature > -10°C	Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30
Change every 500 hours		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %, amb	pient temperature > -10°C	Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 10W-40		
Change every 500 hours		

HYDRAULIC SYSTEM Capacity: 50 liter (Hydraulic tank)

HAMM DOUBLE DRUM COMPACTORS DV/HD HD O70V DEUTZ BF4M1011F (H1520018 ->)



USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 68	Perlus AF 68	Perlus AF 100
Change every 2000 hours		·
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
Change every 2000 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 22	Perlus AF 32	
Change every 2000 hours		
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Change every 2000 hours		
USE		CLIMATE
Biodegradable oil		Cold
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 32		
Change every 2000 hours	•	·

COOLING SYSTEM

Capacity: 13 liter (+ cooler and heater)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.