

HAMM SINGLE DRUM COMPACTORS 3205

DEUTZ F4M2011 (H1580078 ->)

**ENGINE** Deutz F4M-2011

Capacity: 13 liter (Dry fill), Capacity: 10 liter (Service fill)

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50*Change every 50 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40*Change every 50 hours*

| USE | CLIMATE |
|---|---------------|
| Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50*Change every 500 hours*

| USE | CLIMATE |
|---|----------|
| Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C | Moderate |

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40*Change every 500 hours***DIFFERENTIAL**

Capacity: 6,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 250 hours, change every 1000 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 500 hours*

HAMM SINGLE DRUM COMPACTORS 3205

DEUTZ F4M2011 (H1580078 ->)



HUB REDUCTIONS

Capacity: 0,8 liter (each hub)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 250 hours, change every 1000 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 500 hours*

HYDRAULIC SYSTEM

Capacity: 32 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Perlus H 68

PRODUCT RECOMMENDATION 2

Perlus AF 68

PRODUCT RECOMMENDATION 3

Perlus AF 100*Change every 2000 hours*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus AF 46*Change every 2000 hours*

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

PRODUCT RECOMMENDATION 1

Perlus H 32*Change every 2000 hours*

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

PRODUCT RECOMMENDATION 1

Perlus H 22

PRODUCT RECOMMENDATION 2

Perlus AF 32*Change every 2000 hours*

HAMM SINGLE DRUM COMPACTORS 3205

DEUTZ F4M2011 (H1580078 ->)



| USE | | CLIMATE |
|---------------------------|--|----------|
| Biodegradable oil | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 46 | | |

Change every 2000 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Biodegradable oil | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 32 | | |

Change every 2000 hours

| GREASE POINTS/NIPPLES | | |
|--------------------------|---------------------------------|------------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

DRUM GEARBOX

Capacity: 1,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

VIBRATOR

Capacity: 6,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.