# HAMM SINGLE DRUM COMPACTORS 3412 DEUTZ TCD 2012 L04 2V (H1801347 ->)



| <b>ENGINE</b> Deutz TCD 2012 L04 2V Capacity: 11,5 liter (Service fill) |                           |                          |
|---|---------------------------|--------------------------|
| USE   |                           | CLIMATE                  |
| Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C           |                           | Mediterranean            |
| PRODUCT RECOMMENDATION 1  |                           |                          |
| Multifleet SHPD 20W-50  |                           |                          |
| Change every 500 hours  |                           |                          |
| USE   |                           | CLIMATE                  |
| Normal, fuel sulfur level <0,5 %, am                                    | bient temperature > -10°C | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP 10W-40  | Kroontrak CVT 10W-40      | Agrisynth MSP 10W-40     |
| Change every 500 hours  |                           |                          |

| <b>DIFFERENTIAL</b> Capacity: 14 liter  |          |          |
|---|----------|----------|
| USE                                     |          | CLIMATE  |
| Normal                                  |          | Moderate |
| PRODUCT RECOMMENDATION 1                |          |          |
| Gearlube LS 80W-90                      |          |          |
| Check every 250 hours, change every 100 | 00 hours |          |
| USE                                     |          | CLIMATE  |
| Initial service                         |          | Moderate |
| PRODUCT RECOMMENDATION 1                |          |          |
| Gearlube LS 80W-90                      |          |          |
| Change every 500 hours                  |          |          |

| Capacity: 50 liter (Hydraulic tank) |                          |          |
|-------------------------------------|--------------------------|----------|
| USE                                 |                          | CLIMATE  |
| Normal                              |                          | Tropical |
| PRODUCT RECOMMENDATION 1            |                          |          |
| Perlus H 68                         |                          |          |
| Change every 2000 hours             |                          |          |
| USE                                 |                          | CLIMATE  |
| Normal                              |                          | Moderate |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2 |          |
| Perlus Biosynth 46                  | Perlus H 46              |          |
| Change every 2000 hours             |                          |          |
|                                     |                          |          |

HYDRAULIC SYSTEM

## HAMM SINGLE DRUM COMPACTORS 3412 DEUTZ TCD 2012 L04 2V (H1801347 ->)



| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Cold     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| Perlus Biosynth 32       | Perlus H 32              |          |
| Change every 2000 hours  |                          |          |
| USE                      |                          | CLIMATE  |
| Normal                   |                          | Arctic   |
| PRODUCT RECOMMENDATION 1 |                          |          |
| Perlus H 22              |                          |          |
| Change every 2000 hours  |                          |          |
| USE                      |                          | CLIMATE  |
| Biodegradable oil        |                          | Moderate |
| PRODUCT RECOMMENDATION 1 |                          |          |
| Perlus Biosynth 46       |                          |          |
| Change every 2000 hours  |                          |          |
| USE                      |                          | CLIMATE  |
| Biodegradable oil        |                          | Cold     |
| PRODUCT RECOMMENDATION 1 |                          |          |
| Perlus Biosynth 32       |                          |          |
| Change every 2000 hours  |                          |          |

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

### COOLING SYSTEM Capacity: 14 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

#### **DRUM GEARBOX**

Capacity: 3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

#### VIBRATOR

Capacity: 1,6 liter (each side)

We are unable to give a standard recommendation for this component. Please contact our service department.

PRODUCT RECOMMENDATION

### HAMM SINGLE DRUM COMPACTORS 3412 DEUTZ TCD 2012 L04 2V (H1801347 ->)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.