HAMM SINGLE DRUM COMPACTORS 3412 P DEUTZ BF4M2012C (H2140001 ->)



| Agrisynth LSP 10W-40 | Kroontrak CVT 10W-40 | Agrisynth MSP 10W-40 | |
|--|---------------------------|--------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Normal, fuel sulfur level <0,5 %, aml | bient temperature > -10°C | Moderate | |
| USE | | CLIMATE | |
| Change every 500 hours | | | |
| PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 | | | |
| use Normal, fuel sulfur level <0,5 %, aml | bient temperature > -10°C | CLIMATE Mediterranean | |
| ENGINE Deutz BF4M-2012C Capacity: 9,5 liter (Service fill) | | | |

Change every 500 hours

| DIFFERENTIAL Capacity: 14 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |
| Check every 250 hours, change every 1000 hours | | |

| encorrectory zee nears, enange every ree | Revery 200 hours, change every root hours | |
|--|---|----------|
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |

Change every 500 hours

| HYDRAULIC SYSTEM Capacity: 50 liter (Hydraulic tank) | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Perlus H 68 | Perlus AF 68 | Perlus AF 100 |

Change every 2000 hours

| use Normal | | climate Moderate |
|---|---------------------------------------|---------------------|
| PRODUCT RECOMMENDATION 1 Perlus H 46 | PRODUCT RECOMMENDATION 2 Perlus AF 46 | |
| Change every 2000 hours | | |

HAMM SINGLE DRUM COMPACTORS 3412 P DEUTZ BF4M2012C (H2140001 ->)



| USE | | CLIMATE | |
|--------------------------|--------------------------|----------|--|
| Normal | | Cold | |
| PRODUCT RECOMMENDATION 1 | | | |
| Perlus H 32 | | | |
| Change every 2000 hours | | | |
| USE | | CLIMATE | |
| Normal | | Arctic | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Perlus H 22 | Perlus AF 32 | | |
| Change every 2000 hours | | | |
| USE | | CLIMATE | |
| Biodegradable oil | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| Perlus Biosynth 46 | | | |
| Change every 2000 hours | | | |
| USE | | CLIMATE | |
| Biodegradable oil | | Cold | |
| PRODUCT RECOMMENDATION 1 | | | |
| Perlus Biosynth 32 | | | |
| Change every 2000 hours | · | | |
| | | | |

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

COOLING SYSTEM

Capacity: 14 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DRUM GEARBOX

Capacity: 3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

VIBRATOR

Capacity: 1,6 liter (each side)

We are unable to give a standard recommendation for this component. Please contact our service department.

HAMM SINGLE DRUM COMPACTORS 3412 P DEUTZ BF4M2012C (H2140001 ->)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.