## HAMM SINGLE DRUM COMPACTORS 4010 DEUTZ F6L-913



| ENGINE Deutz F6L-913 Capacity: 16 liter |                          |                          |
|---|--------------------------|--------------------------|
| USE                                     |                          | CLIMATE                  |
| Normal                                  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP 10W-40                    | Agrisynth MSP 10W-40     | Agridiesel MSP 15W-40    |

| DIFFERENTIAL<br>Capacity: 13 liter |                             |          |
|------------------------------------|-----------------------------|----------|
| USE                                |                             | CLIMATE  |
| Normal                             |                             | Moderate |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90               | Unigear HS GL-3/GL-5 80W-90 |          |

| HYDRAULIC SYSTEM Capacity: 80 liter |               |
|-------------------------------------|---------------|
| USE                                 | CLIMATE       |
| Normal                              | Mediterranean |
| PRODUCT RECOMMENDATION 1            |               |
| Perlus H 46                         |               |

| HYDROSTATIC DRIVE HYDROSTATIC POWER STEERING |  |               |
|--|--|---------------|
| USE  |  | CLIMATE       |
| Normal                                       |  | Mediterranean |
| PRODUCT RECOMMENDATION 1                     |  |               |
| Perlus H 46                                  |  |               |

| PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|
|                          | Moderate                 |
|                          | CLIMATE                  |
|                          | PRODUCT RECOMMENDATION 2 |

## HAMM SINGLE DRUM COMPACTORS 4010 DEUTZ F6L-913



| INTERMEDIATE GEARS       |                             |          |
|--------------------------|-----------------------------|----------|
| USE                      |                             | CLIMATE  |
| Normal                   |                             | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |

| VIBRATOR HOUSINGS<br>Capacity: 1,6 liter |          |
|--|----------|
| USE                                      | CLIMATE  |
| Normal                                   | Moderate |
| PRODUCT RECOMMENDATION 1                 |          |
| Gearlube GL-4 80W-90                     |          |

| WHEEL SPEED REDUCTION GEARS Capacity: 1,9 liter |                             |          |
|---|-----------------------------|----------|
| USE   |                             | CLIMATE  |
| Normal  |                             | Moderate |
| PRODUCT RECOMMENDATION 1                        | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                            | Unigear HS GL-3/GL-5 80W-90 |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.