

# HANGCHA FORKLIFT TRUCKS N-SERIES

## CPCD30N YANMAR 4TNV94L



**ENGINE** Yanmar 4TNV94L  
Capacity: 6,5-7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Check every 8 hours, change every 100 hours*

**DIFFERENTIAL FRONT**  
Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1200 hours*

**TRANSMISSION**  
Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	

*Change every 1200 hours*

**HYDRAULIC SYSTEM**  
Capacity: 45-50 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Change every 1200 hours*

**HYDRAULIC BRAKE SYSTEM**  
Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Change every 1200 hours*

# HANGCHA FORKLIFT TRUCKS N-SERIES

## CPCD30N YANMAR 4TNV94L



### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 8 hours, change every 100 hours*

### COOLING SYSTEM

Capacity: 10-11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 1200 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*