

# HANGCHA FORKLIFT TRUCKS N-SERIES

## CPCD35N CUMMINS B3.3

**ENGINE** Cummins B3.3

Capacity: 6,5-7,5 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

## PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40***Check every 8 hours, change every 100 hours***DIFFERENTIAL FRONT**

Capacity: 8 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 1200 hours***TRANSMISSION**

Capacity: 7 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 2032**

## PRODUCT RECOMMENDATION 2

**ATF Almirol***Change every 1200 hours***HYDRAULIC SYSTEM**

Capacity: 45-50 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Perlus H 32***Change every 1200 hours***HYDRAULIC BRAKE SYSTEM**

Capacity: 1,5 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Change every 1200 hours*

# HANGCHA FORKLIFT TRUCKS N-SERIES

## CPCD35N CUMMINS B3.3



### GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Check every 8 hours, change every 100 hours*

### COOLING SYSTEM

Capacity: 10-11 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Change every 1200 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*